

**NOVAX**<sup>®</sup>  
PREMIUM AUTO REFINISH

**NOVAX**<sup>®</sup>  
PREMIUM AUTO REFINISH



**NX**<sup>®</sup>  
PT. NOVAX PAINT INDONESIA

PT. NOVAX PAINT INDONESIA	
📍	JL. CENGKEH 22M, DKI JAKARTA
🌐	novaxpaint.id@gmail.com
📷	@novaxpaint.id



NOVAX PAINT is a global brand of refinishing coatings designed specifically for auto body repair shops. We deliver enhanced productivity throughout the entire workshop with coating systems engineered for easy, fast, and accurate application. In addition, we offer localized business and marketing support, along with practical innovations that simplify and accelerate the refinishing process. Through our products and services, we empower auto body repair shops to drive their business forward.

### NOVAX THINNER SLOW DRY

#### Descriptions

Novax Thinner Extra Slow is a slow-evaporating solvent blend designed to prolong the open time of 1K and 2K products. It enhances overspray melt-in and optimizes flow, especially under high-temperature conditions.



QUICK DRY



HIGH GLOSS



GREAT COVERAGE




HIGH DURABILITY



UV RESISTANT

## Easy, Fast, and Excellent Result



**NX PU Primer Surfacer**

**Descriptions**

NX PU Primer Surfacer is an extremely versatile 2K primer surfacer, it can be applied directly over metal, and over putty. It delivers a smooth and durable surface and can be mixed for a wide range of application windows. It is suitable for all topcoats and basecoats from Novax.



**TECHNICAL DATA**

**Mixing Ratio**

	- NX PU Primer Surfacer : 4 (by volume)
	- NX PUP Hardener : 1 (by volume)
	- Novax Thinner Slow Dry : 3 (by volume)

**Spraying Viscosity**

	Viscosity / sec : 30°C
	NK <sup>2</sup> : 10-11 mm

**Drying Time**

	Touch Dry : 10 minutes
	Sanding Time : 30 minutes
	Pot Life (Hours) : 5 hours

**Thickness**

Film Thickness (One Coat) : 30 micron

**NX Epoxy Primer Surfacer**

**Descriptions**

NX Epoxy Primer Surfacer is 2K epoxy primer surfacer. It is chromate free and offers very good resistance to corrosion, humidity and chemicals. It is suitable for use over many different substrates.



**TECHNICAL DATA**

**Mixing Ratio**

	- NX Epoxy Primer Surfacer : 4 (by volume)
	- NX PSEP Hardener : 1 (by volume)
	- Novax Thinner Slow Dry : 2 (by volume)

**Drying Time**

	Touch Dry : ±20 minutes
	Sanding Time : 3 hours
	Pot Life (Hours) : 5 - 6 hours

**CC 306M**

**Descriptions**

Clear Coat 306M is a user-friendly, low-emission 2K clear coat. It delivers a durable finish with excellent anti-graffiti properties. This product provides a smooth, solid surface with outstanding gloss retention and superior chemical resistance. Ideal for spot, panel, and complete body repairs.



**TECHNICAL DATA**

**Mixing Ratio**

	- CC 306 M Clear 2 (by volume)
	- CC 306 M Hardener 1 (by volume)
	- Novax Thinner Slow Dry : 20-25% (by volume)

**Spraying Viscosity**

	Viscosity / sec : 30°C
	NK <sup>2</sup> : 9-11 mm

**Spray Gun Gravity Feed**

	Set-up : Full pattern, flow -3 turns from fully closed set-up
	Nozzle Size : 1,3 - 1,5 mm
	Spray Pressure : 1,5 - 2.0 bar

**Drying Time**

	Flash off : 5 minutes (30°C)
	Drying Time : - Surface Dry : 7 minutes
	- Hard Dry : 6 hours
	- Dry to Spot Repair : > 1 hour ( 30°C )

**CC 205 F**


**Descriptions**

Clear Coat 205F offers fast drying at any temperature and maintains the texture of the coating well, ensuring ease of application. This formulation delivers reliable results under various operating conditions. It is part of the Clear Coat 205 F system.



**TECHNICAL DATA**

**Mixing Ratio**



- CC 205 F Clear 4 (by volume)
- CC 205 F Hardener 1 (by volume)
- Novax Thinner Slow Dry : 20-30% (by volume)

**Spraying Viscosity**



Viscosity / sec : 30°C  
NK<sup>2</sup> : 9-11 mm



**Spray Gun Gravity Feed**  
Set-up : Full pattern, flow -3 turns form fully closed set-up  
Nozzle Size : 1,3 - 1,5 mm  
Spray Pressure : 1,5 - 2.0 bar

**Drying Time**



Flash off : 2-5 minutes (30°C)  
Drying Time : - Surface Dry : 4 minutes  
- Hard Dry : 4 hours  
- Dry to Spot Repair : > 1 hour ( 30°C )

**NX BASECOAT SERIES**


**Descriptions**

NX Basecoat Series is a high quality solvent based polyurethane base coat, designed to enhance your vehicle with superior results. Using a concentrated color and binder system, NX Basecoat Series combines high opacity with low material consumption, resulting in outstanding refinishing performance. Its versatile application and wide color range help increase productivity in the workshop.



**TECHNICAL DATA**

**Mixing Ratio**



- NX Basecoat Series 1 (by volume)
- Thinner PU Slow Dry : 40-50% (by volume)

**Drying Time**



Flash off : 1 minute  
Hard Dry : 15 minutes  
(@30°C, 2-3 layers)

**NX BASECOAT READY MIX**


**Descriptions**

NX Basecoat Ready Mix is a high-performance basecoat formulated with a ready-to-use polyurethane solvent system. Engineered for high productivity, it delivers accurate color matching and stability. NX Basecoat Ready Mix is designed based on the formulations of units on the market to simplify, speed up and increase productivity in the workshop. It enhances efficiency and consistency in body shop operations.



**TECHNICAL DATA**

**Mixing Ratio**



- NX Basecoat Ready Mix : 1 (by volume)
- Thinner PU Slow Dry : 40-50% (by volume)

**Drying Time**



Flash off : 1 minute  
Hard Dry : 15 minutes  
(@30°C, 2-3 layers)